




N-Channel Enhancement Mode Field Effect Transistor



Product Summary

- V_{DS} 100V
- I_D 15A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) $<110m\Omega$
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) $<120m\Omega$
- 100% EAS Tested
- 100% ∇V_{DS} Tested

General Description

- Trench Power MV MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- DC-DC Converters
- Power management functions

■ Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	100	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_C=25^\circ\text{C}$	I_D	15	A
	$T_C=100^\circ\text{C}$		9.5	
Pulsed Drain Current ^A		I_{DM}	60	A
Single Pulse Avalanche Energy ^B		E_{AS}	9	mJ
Total Power Dissipation	$T_C=25^\circ\text{C}$	P_D	28	W
	$T_C=100^\circ\text{C}$		11	W
Thermal Resistance Junction-to-Case ^C		$R_{\theta JC}$	4.4	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range		T_J, T_{STG}	$-55\sim+150$	$^\circ\text{C}$

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJD15N10A	F1/F2	YJD15N10A	2500	/	25000	13" reel



YJD15N10A

RECOMMEND
YJD12N10B
FOR NEW DESIGN

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Static Parameter							
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =250μA		100			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100V, V _{GS} =0V	T _J =25℃			1	μA
			T _J =150℃			100	
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V				±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA		1.1	1.8	2.5	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D =8A			95	110	mΩ
		V _{GS} = 4.5V, I _D =8A			100	120	
Diode Forward Voltage	V _{SD}	I _S =15A, V _{GS} =0V			0.8	1.2	V
Maximum Body-Diode Continuous Current	I _S					15	A
Dynamic Parameters							
Input Capacitance	C _{iss}	V _{DS} =50V, V _{GS} =0V, f=1MHZ			1070		pF
Output Capacitance	C _{oss}				33		
Reverse Transfer Capacitance	C _{rss}				30		
Switching Parameters							
Total Gate Charge	Q _g	V _{GS} =10V, V _{DS} =50V, I _D =10A			26		nC
Gate-Source Charge	Q _{gs}				5.4		
Gate-Drain Charge	Q _{gd}				5.8		
Reverse Recovery Charge	Q _{rr}	I _F =10A, di/dt=100A/us			30.1		ns
Reverse Recovery Time	t _{rr}				40		
Turn-on Delay Time	t _{D(on)}	V _{GS} =10V, V _{DD} =50V, R _L =6.4Ω R _{GEN} =3Ω			7		
Turn-on Rise Time	t _r				24		
Turn-off Delay Time	t _{D(off)}				24		
Turn-off fall Time	t _f				31		

A. Pulse Test: Pulse Width≤300us, Duty cycle ≤2%.

B. T_J=25℃, V_{DD}=50V, V_G=10V, L=0.5mH, I_{AS}=6A

C. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins. R_{θJC} is guaranteed by design, while R_{θJA} is determined by the board design. The maximum rating presented here is based on mounting on a 1 in 2 pad of 2oz copper



■ Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance vs. Junction Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge




Figure 7. Safe Operation Area




Figure 8. Maximum Continuous Drain Current vs Case Temperature




Figure 9. On-Resistance vs Gate to Source Voltage




Figure 10. Forward characteristics of reverse diode




Figure 11. Normalized Threshold voltage




Figure 12. Power dissipation








Figure 13. Normalized Maximum Transient Thermal Impedance






Unclamped Inductive Switching (UIS) Test Circuit & Waveforms


TO-252-B Package information




TOP VIEW



BOTTOM VIEW



SIDE VIEW




SUGGESTED SOLDER PAD LAYOUT

SYMBOL	DIMENSIONS					
	INCHES			Millimeter		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A1	0.000	---	0.008	0.000	---	0.200
A2	0.087	0.091	0.094	2.200	2.300	2.400
A3	0.035	0.039	0.043	0.900	1.000	1.100
b	0.026	0.030	0.034	0.660	0.760	0.860
c	0.018	0.020	0.023	0.460	0.520	0.580
D	0.256	0.260	0.264	6.500	6.600	6.700
D1	0.203	0.209	0.215	5.150	5.300	5.450
D2	0.181	0.189	0.195	4.600	4.800	4.950
E	0.390	0.398	0.406	9.900	10.100	10.300
E1	0.236	0.240	0.244	6.000	6.100	6.200
E2	0.203	0.209	0.215	5.150	5.300	5.450
e	0.090BSC			2.286BSC		
L	0.049	0.059	0.069	1.250	1.500	1.750
L1	0.035	---	0.050	0.900	---	1.270
L2	0.055	---	0.075	1.400	---	1.900
L3	0.024	0.031	0.039	0.600	0.800	1.000
L4	0.114REF			2.900REF		
θ	0°	---	10°	0°	---	10°

NOTE:

1. PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2. TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3. THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

■ Marking Information



Note:

1. All marking is at middle of the product body
2. All marking is in laser printing
3. YJD15N10A is part no., YYWW is date code, "YY" is year, "WW" is week
4. Body color: Black

NOT RECOMMEND
FOR NEW DESIGN



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.

NOT RECOMMEND
FOR NEW DESIGN